NL Handleiding Verlaagd Bankje




Onderdelen

1. Bankje
2. Ondersteuningsplaten (L en R)
3. Meegeleverde schroeven

Stap 1: Demontage

Demonteer het huidige bankje door deze los te schroeven.

Let op: De ondersteuningslatten en schroeven moeten worden hergebruikt.





Stap 2: Hoogte bepaling

Bepaal de juiste hoogte. Op de hoogste positie hoeft er niet in het bankje gezaagd te worden. Voor de 2e of 3e positie moeten respectievelijk de 1e of 2e zaagsnede doorgezaagd worden.

Let op: Afgezaagd kan het bankje niet meer hoger worden geplaatst.

Stap 3: Montage ondersteuningslatten

Schroef de bevestigingslatten vast op de gekozen positie. Doe dit met de originele schroeven.





Stap 4: Assemblage bankje

Plaats het bankje op de bevestigingslatten en schroef deze van met de lange parker schroeven.

Let op: Niet te strak aandraaien.

Stap 5: Montage bankje in de bak

Plaats het verlaagde bankje in de bak en monteer deze aan beide kanten met de schroeven.






Stap 6: Montage gordels

Bevestig de onderkant van de gordels aan het bankje met de originele schroeven.

Let op: Zorg ervoor dat de lengte van de gordels opnieuw wordt afgesteld.

Stap 7: Afwerking van de bak

Met de twee overgebleven schroeven kunt u de twee niet gebruikte gaten in de bak opvullen. Dit is puur cosmetisch.






Parts overview

1. Seat
2. Support plates (L and R)
3. Supplied screws

Step 1: Disassembly

Disassemble the old seat by unscrewing it.



Note: The support slats and screws pictured here need to be re-used.



Step 2: Height assessment

Determine the correct height. When choosing the highest position there is no need to saw. When choosing the 2nd or 3rd you have to shorten the bench by sawing of the 1st or 2nd slit respectively.

Note: Once shortened, the bench can not be used in a higher position.

Step 3: Mount the support slats

Attach the support slats to the support plates on the desired height.
Use the original screws.





Step 4: Assembly of the bench

Place the seat support slats and secure it by using the long parker screws.

Note: Do not overtighten the screws.

Step 5: Mount the lowered bench

Place the bench in de box. Secure it with the supplied screws.





Step 6: Mount the seatbelts

Secure the seatbelts back to the bench with the original screws.

Note: Readjust the length of the seatbelts if deemed necessary.

Step 7: Finishing touches

With the two remaining screws you can plug-up the two holes left in the box. This is purely cosmetic.

